

Zabbix

Zabbix is an open-source enterprise-class distributed monitoring solution.

You can find information about Zabbix on the [official Zabbix page](#).

You can also try Zabbix as a [ready-made solution](#) or install it using [Zabbix documentation](#).

Integration with Zabbix

Integration with the Zabbix monitoring system is possible in two modes:

1. **Active mode**, where connection to Zabbix server is initialized by SafeUTM. To set up this mode, fill in the following fields:

- **SafeUTM hostname** that will be displayed on the monitoring server.
- **Server Address** – IP address, domain name, or IP-address:port, domain name:port in cases where an incoming port that is not standard for Zabbix is used. To add one more address, click **Add Address**.

2. **Passive mode**, where the connection is initiated by the Zabbix server. To set up this mode, fill in the following fields:

- **Connection port** – choose port 10050 or 10051.
- **Server Address** – IP address or domain name of Zabbix servers. To add one more address, click **Add Address**.

Zabbix

Stopped

☒ Zabbix agent

☒ Sending data to Zabbix (active mode)

Hostname Safe UTM

test.test

Server address

192.168.100.30

IP address or domain_name, IP address:port or
domain_name:port

Add address

☒ Receive requests from Zabbix (passive mode)

Connection port:

☐ 10050 ☒ 10051

Server address

192.168.100.60

IP-address or domain name

Add address

Save

In both cases of integration, the Zabbix server must be located inside the SafeUTM LAN. Monitoring can only be connected to local interfaces.

Standard templates for Linux servers can be used as data templates.

Revision #5

Created 25 August 2022 01:01:15 by Val Redman

Updated 13 October 2022 14:55:14 by Val Redman