

Configuring PPPoE Connection

Connection via PPPoE protocol is traditionally used by providers offering connection via xDSL.

To configure the connection in the web interface, follow these steps:

1. Go to menu **Services -> Network Interfaces**.
2. Click on the icon (+) in the upper right corner of the window and select **Ethernet + PPPoE**.
3. Select a network card.
4. Fill in the fields listed in the table below:

Parameter	Description
Title	The name you will use to identify the interface in the future. Maximum 42 characters.
Network card	The network adapter will be used to connect to the Internet provider.
VLAN tag	The VLAN ID in which UTM will be present Such network interface is considered a VLAN interface. Fill in only if the network card is already in use.
Login	Username for PPPoE connection.
Password	Password for PPPoE connection.
Service	Service ID. If you don't know what to enter, leave the field empty.
Access concentrator (Hub)	Hub ID. If you don't know what to enter, leave the field empty.

5. Make sure the entered values are correct and click **Save**.

Configuration example:


Network Interfaces

Configure external Ethernet + PPPoE interface

Title

Ethernet

Network card Intel Corporation 82540EM Gigabit Ethernet Controller 


MAC address 08:00:27:fb:fb:a9 

VLAN

Number from 1 to 4094

PPPoE

Login

Password 

Service (optional)

Access concentrator (optional)

Save

Cancel

Revision #4

Created 25 August 2022 20:55:11 by Val Redman

Updated 13 October 2022 15:16:11 by Val Redman