Allow Internet to Everyone

This mode is used to diagnose problems.

Active **Allow Internet to everyone** mode does not automatically turn off and works until you turn it off.


In this case:

- **Firewall** rules won't work.
- Traffic filtering will not occur.
- Web statistics will not be collected.
- Users will be allowed to access the Internet without authorization.

There are two ways to enable this mode:

1. In the web interface.

To do this, click on the technical support icon in the upper right part of the window, and in the window that opens, drag the mode activation slider to the **Active** position**.**



2. In the local menu.

To do this, enter number **6.** Enable **'Allow Internet to all'** mode and press **Enter** to apply the setting.

```
Server management

1. Shell
2. Configuring a local network interface
3. Disable access to the web interface from WAN
4. Disable access to the server via SSH from WAN
5. Disable access to the server via SSH from LAN
6. Enable `Allow Internet Access to All`
7. Flush IP bans
8. Enable user's firewall
9. Create new backup
10. Restore backup
11. Enable Remote Assistant
12. Technical support contacts
13. Edit server name
14. Create cluster
15. Rollback to the previous version
16. Reboot
17. Shutdown
18. Exit

Type your choice and press Enter.
# 6
Settings changed successfully.
```

Revision #5
Created 2022-08-27 20:45:37 UTC by Val Redman
Updated 2022-10-13 16:11:03 UTC by Val Redman