

y.api

About y-api service

The service provides domain categorization services and can be used both locally and in a distributed system. In the latter case, the speed of receiving a response decreases due to network delays.

A stable connection to the Internet is required for the uninterrupted operation of the service:

- loading the database and updating it
- sending counter_cat and counter_unknown_cat values
- sending additional information about the instance with the container

Stats are sent every 5 minutes.

Using y-api service

Starting the service

1. Install docker.
2. Load the archive with the container image with `sudo docker load -i y_api.tar.gz`
3. Run the image in the docker subnet.
 - 3.1 Alternatively, create a separate subnet
`sudo docker network create --driver=bridge --subnet=193.33.33.0/24 y-api-net`
and run the container
`sudo docker run -it -d --net y-api-net --ip 193.33.33.33 y-api:1`
4. Check the service with `curl http://193.33.33.33/qwerty.com`

193.33.33.33 is an example, you can use any other network.

Service response: `{"category": [36, 49], "bad": false, "category_name": ["Education", "Computers & Internet"]}`

ATTENTION! The request counter is sent every 5 minutes. Check time must be shorter so the data is not sent to the statistics server for billing.

Logging is done to **stdout** and **stderr**.

The supported request is **GET**.

Request examples

Request	Answer
<code>curl -v http://193.33.33.33/qwerty.com</code>	< HTTP/1.1 200 OK < Content-type: application/json < Connection: keep-alive * no chunk, no close, no size. Assume close to signal end < * Closing connection 0 { "category": [36, 49], "bad": false, "category_name": ["Education", "Computers & Internet"] }
<code>curl -v http://193.33.33.33/foo</code>	< HTTP/1.1 404 Not Found < Connection: keep-alive * Connection #0 to host 193.33.33.33 left intact
<code>curl -v http://193.33.33.33/stat/</code>	< HTTP/1.1 200 OK < Content-type: application/json < Connection: close < * Closing connection 0 { "counter_cat": [150002], "counter_unknown_cat": [0] }
<code>curl -v -X POST http://193.33.33.33/qwerty.com</code>	< HTTP/1.1 405 Method Not Allowed < Content-Type: text/html < Allow: GET < Connection: close * Closing connection 0
If there is no connection with the statistics server or any response from it other than "200 OK". <code>curl -v http://193.33.33.33/qwerty.com</code>	< HTTP/1.1 503 Service Unavailable < Content-type: application/json < Connection: close < * Closing connection 0 { "details": "billing failure" }

Revision #3

Created 28 December 2023 05:40:10 by Amy Drake

Updated 28 December 2023 08:27:14 by Amy Drake